LCF-300-S Precision Fluid Damped Inclinometer
0-5V DC Output

Jewell Instruments

Making Sense out of Motion…

The LCF-300 Series Inclinometer is a rugged, high performance, single-axis tilt sensor designed for peak performance in extreme conditions. The fluid damped mechanism delivers superior noise rejection in high shock and vibration environments as well as excellent output stability. Units are available with a 6-pin connector or pin-terminals. Custom input ranges, filters and temperature compensation are also available on request.

Features

- ***Resolution of 1 µrad***
- ***Temperature Compensation Available***
- ***0-5V Output***
- ***+9 to +18 Volts DC Power Input***
- ***RoHS Compliant***

Applications

- ***High-precision Geotech***
- ***Oil and Gas, Riser Tilt Monitoring***
- ***Railroad MOW Equipment***
- ***Pavement Profiling Rigs***
- ***Vehicle Wheel Alignment***
- ***Robotics***

RoHS COMPLIANT

Connector Version

PIN	FUNCTION
	SINGLE SUPPLY
A	+ VDC
B	PWR / SIG COM
C	N/C
D	SIG OUT
E	N/C
F	N/C



Pin Terminal Version

PIN	FUNCTION
	SINGLE SUPPLY
A	+ VDC
B	N/C
C	PWR / SIG COM
D	SIG OUT



Jewell Instruments LLC 850 Perimeter Road, Manchester, NH 03103
sales@jewellinstruments.com • www.jewellinstruments.com • Tel (800) 227-5955

LCF-300-S Precision Fluid Damped Inclinometer
0-5V DC Output

Jewell Instruments

Making Sense out of Motion…

STATIC/DYNAMIC

Input Range (deg.)	±1	±3	±14.5	±30	±60	±90
Full Range Output (VDC)[1] ±0.5%	0-5	0-5	0-5	0-5	0-5	0-5
Non-linearity (% FRO max.)[2]	0.05	0.04	0.02	0.02	0.02	0.02
Scale Factor (V/g nom.)	143.2	47.8	10.0	5.0	2.9	2.5
Scale Factor Temp. Sensitivity (PPM/°C max)	350	150	100	60	60	60
Bandwidth, Hz (-3 dB) nominal	0.5	2	15	20	30	30
Transverse Axis Misalignment (° max)	0.25	0.5	0.5	0.5	1.0	1.0
0° Output nominal (V)	2.48 to 2.52					
0° Output Temp. Sensitivity (V/°C max)	0.015	0.005	0.001	0.0005	0.0004	0.0003
Resolution & Threshold (µradians)[3] max	1	1	1	1	1	1

[1]Full Range is defined "from negative full input angle to positive full input angle." [2]Nonlinearity is specified as deviation of output referenced to theoretical sine function value, independent of misalignment. [3]Full Resolution is achieved with noise reduction techniques.

ELECTRICAL

Number of Axes:	1
Input Voltage Range, (VDC):	+9 to +18
Input Current, mA, max:	40
Noise, Vrms, maximum:	0.002
Output Impedance (ohms)	1

ENVIRONMENTAL

Operating Temp Range:	-40°C to +80°C
Storage Temp Range:	-60°C to +90°C
Shock:	1500g, 0.5 msec, ½ sine
Seal	IP65

PHYSICAL

Mass (grams)	230

How to order:



Jewell Instruments LLC 850 Perimeter Road, Manchester, NH 03103
sales@jewellinstruments.com • www.jewellinstruments.com • Tel (800) 227-5955

Outline Drawing: Connector Version



Outline Drawing: Pin Terminal Version